

Fork: FOX 40 Float FIT GRIP2 EVOL Factory Kashima 203 mm

Follow FOX 40 recommended settings on the left back side of the casting.

Mondraker recommended FOX 40 Float FIT GRIP2 Factory Kashima settings based on Rider weight & Downhill application:

SAG		RECOMMENDED SETTING*			
rider weight	air pressure	clik(s) from full open			
lbs / kg	psi	HSR	LSR	HSC	LSC
120 / 54	49	1	5-6	1-4	1-3
140 / 64	56	2-3	6-7	3-7	3-5
160 / 73	63	3-4	7-8	6-10	5-7
180 / 82	70	4-5	8-9	9-13	7-9
200 / 91	77	5-6	9-10	12-16	9-11
220 / 100	84	6-7	10-11	15-19	11-13
240 / 109	91	7-8	11-12	18-22	13-15

Suggested fork sag 20%

Rear shock: FOX DHX2 Factory Kashima

Size S: 450 lbs **Size M:** 500 lbs **Size L/XL:** 550 lbs

SAG		RECOMMENDED SETTING*			
rider weight	spring rate	clik(s) from full open			
lbs / kg	lbs	HSC	LSC	HSR	LSR
120 / 54	450	1	2	3	3
140 / 64	450	2	3	4	4
160 / 73	500	3	4	5	5
180 / 82	500	4	5	5	6
200 / 91	550	5	6	6	7
220 / 100	550	6	7	7	8
240 / 109	550	7	8	8	9

** These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions*

Settings based on Downhill application & 35% recommended sag