

Fork: FOX 36 Float FIT GRIP2 EVOL Factory Kashima 170 mm

Follow FOX 36 recommended settings on the left back side of the casting.

Mondraker recommended FOX 36 FIT GRIP2 fork settings based on Rider weight & Enduro application:

SAG		RECOMMENDED SETTING*			
rider weight	air pressure	clik(s) from full open			
lbs / kg	psi	HSR	LSR	HSC	LSC
120 / 54	55	1	5-6	1-4	1-3
140 / 64	64	2-3	6-7	3-7	3-5
160 / 73	73	3-4	7-8	6-10	5-7
180 / 82	82	4-5	8-9	9-13	7-9
200 / 91	91	5-6	9-10	12-16	9-11
220 / 100	100	6-7	10-11	15-19	11-13
240 / 109	109	7-8	11-12	18-22	13-15

Suggested fork sag 20%

Rear shock: FOX DHX2 Factory Kashima

Size S: 400 lbs **Size M:** 450 lbs **Size L/XL:** 500 lbs

SAG		RECOMMENDED SETTING*			
rider weight	spring rate	clik(s) from full open			
lbs / kg	lbs	HSC	LSC	HSR	LSR
120 / 54	400	1	2	1	2
140 / 64	400	2	3	2	3
160 / 73	450	3	4	3	3
180 / 82	450	4	5	3	4
200 / 91	500	5	6	4	5
220 / 100	500	6	7	5	6
240 / 109	500	7	8	6	7

** These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions*

Settings based on Enduro application & 30-35% recommended sag. Add 2-3 clics each setting for a more controlled "XC-style" ride